REEFER POWER PRODUCTSPANEL SPECIFICATIONS



Product Code: MT-10B-Y

10-Gang Distribution Tree

- 10-gang outlet assembly equipped with RPP safety-interlocked outlets.
- NEMA 4X enclosure, constructed from 14GA seam-welded stainless steel. Powder-coated in Grey/Yellow.
- Features (10) RPP 47052 32-amp safety-interlocked outlets, wired internally to a power distribution block (PDB).
- Each outlet includes a lockable ON/OFF switch to ensure safe power control.
- Equipped with a UL489 Listed circuit breakers, providing overcurrent protection for each outlet.
- Includes (1) set of 400A male Camlock-style receptacles for incoming power.
- Set of 400A female Camlock-style receptacles for outgoing power, optional.
- Features a gasketed rear access cover with a drip shield.
- Designed with forklift pockets for easy mobility; pockets come with anchor bolt holes for permanent installation.

Specifications

10-Gang Assembly

400A 480VAC (380/480VAC 50/60hz) 3 phase 3 wire + ground

Receptacles

32A 480VAC (380/440VAC 50/60 Hz) 3h

Circuit Breakers

32A trip, 10,000AIC @ 480VAC

Enclosure

• Type NEMA 4X/IP66, 304 SS, Powder Coated, Rear Access Cover

Input/Output Cams

• (1 set each) Cam-type single pole receptacles, 400A, 600VAC (3 phase + ground) (green, brown, orange, yellow)

Approx. Weight

• 200lbs.

Approvals

- UL 489 Listed / Circuit Breakers
- IEC/CEI/EN 60309-1, 603309-2
- Low Voltage Directive 2014/35/UE











