REEFER POWER PRODUCTSPANEL SPECIFICATIONS



Product Code: MT-4B-N

4-Gang Distribution Tree

- 4-gang outlet assembly equipped with RPP safety-interlocked outlets.
- NEMA 4X enclosure, constructed from 14GA seam-welded stainless steel.
- Features (4) RPP 47052 32-amp safety-interlocked outlets, wired internally to a power distribution block (PDB).
- Each outlet includes a lockable ON/OFF switch to ensure safe power control.
- Equipped with a UL489 Listed circuit breaker, providing overcurrent protection for each outlet.
- Designed for hardwire power input.
- Includes mounting tabs for surface mount installation.
- Includes hinged front access door.

Specifications

4-Gang Assembly • 130A 480VAC (380/480VAC 50/60hz) 3 phase 3 wire + ground

Receptacles • 32A 480VAC (380/440VAC 50/60 Hz) 3h

Circuit Breakers • 32A trip, 10,000AIC @ 480VAC

Type NEMA 4X/IP66, 316 SS

Power Input • Designed for top, bottom or rear cable entry.

Approx. Weight • 50lbs.

Approvals

- UL 489 Listed / Circuit Breakers
- IEC/CEI/EN 60309-1, 603309-2
- Low Voltage Directive 2014/35/UE

Drawing









